

# Felt 9900

Sterling 3057

## Specifications

---

### Contents

100% polyester

### Weight

10.2 oz/lin.yard

### Width

64" useable

### Repeat

none

### Treatment

### Backing

## Cleaning Code

---

<p>Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.</p>

## Performance

---



### Breaking Strength (ASTM D5034)

138 lbf min. warp and 96 lbf min. fill

### Tear (ASTM D2261)

99 lbf min. warp and 47 lbf min. fill

### Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

### Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 4 min. wet

### Flammability

ASTM E84 Class I or A

### NRC of anechoic termination

1.00

### NRC of fabric in front of anechoic termination

0.99


## Miscellaneous

---

Proudly made in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a non-directional fabric.

This product is a Feltvari™ non-woven.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

Acoustical Performance for Panel Applications  
(ISO 10534-2)

