

# Clarity 5581

Calm 308

## Specifications

---

### Contents

63% post-consumer recycled polyester  
37% antimony-free polyester

### Weight

14.6 ± 1.5 oz./lin. yd.

### Width

54" min. useable

### Repeat

3.75" vertical, 5.4" horizontal

### Treatment

Crypton Green stain resistance  
Crypton Green odor resistance

### Backing

Crypton Green moisture barrier

### Treatment

Crypton Green stain resistance  
Crypton Green odor resistance

### Backing

Crypton Green moisture barrier

## Cleaning Code

---

<p>Standard Care Label W. Clean with water based cleaning agents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.</p>

## Performance

---



### Breaking Strength (ASTM D5034)

200 lbf min. warp and 155 lbf min. fill

### Tear (ASTM D2261)

25 lbf min. warp and fill

### Seam Slippage (ASTM D4034)

105 lbf warp and 85 lbf fill

### Pilling resistance (ASTM D3511)

Class 4 min.

### Colorfastness to light (AATCC 16.3 Option 3)

Grade 4 min. at 40 hours

### Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

### Wyzenbeek Abrasion resistance (ASTM D4157)

100,000 double rubs cotton duck

### Flammability

CA Technical Bulletin 117-2013 Section 1

## Miscellaneous

---

Every effort has been made to ensure color accuracy of the digital images, however, please order a sample before specification. Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Proudly woven in North America supporting our local communities.

